

NL432PV

NHP NLINE Enclosed DC Isolating Switch, IP66NW Plastic, 4 Pole 32A 1500V DC (DC-PV2)



Component type	Switch disconnecter
Range	NLINE Weatherproof Isolators
Model	N/A
Product status	Existing

NHP's NLINE weatherproof isolating switches are available in three current ratings and feature a large isolator handle for easy operation. A special gasket, stainless steel cover and screws increases ingress protection. The body is made of UV-resistant polycarbonate to offer extended life in outdoor applications. All switches are tested and approved to AS/NZS3133.

ELECTRICAL

Rated operating voltage Ue	1500 V
Rated permanent current Iu	32 A
Number of poles	4
Rated operation current Ie at DC-23, 220 V	32 A
Rated operation current Ie at DC-23a, 500 V	32 A
Rated insulation voltage Ui	1500 V
Rated impulse withstand voltage Uimp	8 kV
Rated operating voltage	1500 V

CONSTRUCTION

Colour control element	Grey
Degree of protection (IP), front side	IP66
Version as reversing switch	No
Suitable for floor mounting	No

DIMENSIONS

Height	180 mm
Width	99 mm
Depth	107 mm
Connectable conductor cross section	4-16 mm ²

ENVIRONMENT

Rated surrounding temperature without derating	85 °C
--	-------

RELATED PRODUCTS


ACCESSORY



Item No: NLA432PVBL

Required: No

Description: NHP NLINE Bridging Links, suits NL432PV (QTY 4)



Item No: NLARDM25M12

Required: No

Description: NHP NLINE Threaded Reducer M25 to M12, suits NL432PV (QTY 4)

NL432PV

NHP NLINE Enclosed DC Isolating Switch, IP66NW Plastic, 4 Pole 32A 1500V DC (DC-PV2)



RELATED PRODUCTS

ACCESSORY



Item No: NLAWMB

Required: No

Description: NHP NLINE Wall Mount Brackets, suits NL432PV (QTY 2)